

FT2306-FFP1

Respirator



The masks offer half-face coverage with 2 headband style straps for a secure fit. The cupped design offers low breathing resistance and is ergonomically designed for comfort.

Descriptions
MATERIAL OF BODY PART
4 Ply Nonwoven
Outer layer: 30g PP+100g needle-punched fabric
Middle layer: 38g melt blown fabric
Inner layer: 160g needle-punched fabric
MATERIAL OF NOSE CLIP
Adjustable Aluminum Braided
MATERIAL OF HEAD ON STRIP
Spandex elastic
SPONGE BAR
Polyurethane (PU) foam
SIZE
One size
BREATHING VALVE DEVICE
No
PRODUCTION METHOD
Ultrasonic welded
REUSABLE
No
STYLE
Cup shape mask
PACKAGE

20 PCS/BOX
400PCS/CTN
Carton dimension: 69*28.5*46.5CM
Net weight: 4.3KG
Gross weight: 6.7KG



Certification
Safety masks meet the European standard EN149:2001+A1:2009 FFP1 standard requirements



Product parameters
Inspiratory resistance(30LPM±1LPM): ≤6MMH2O
Inspiratory resistance(95LPM±1LPM): ≤21MMH2O
Filtration efficiency(salt spray 1%): ≥80%
Filtration efficiency(paraffin oil or DOP 1%): ≥80%
Headband tension: 20N/10s

Product features

- CE FFP1 CERTIFIED: FFP1 masks remove at least 80% of non-oil-based particles down to 0.3 microns.
- COMFORTABLE & ADJUSTABLE: High quality, light weight construction provides comfort, while the adjustable nose clip with foam and heavy duty straps conforms to your facial features for an enhanced seal.
- BREATHE EASY: Built-in exhalation cool valve reduces heat, moisture, and humidity build-up, to keep you more comfortable longer
- Common Uses: Prevents particulate matter from the processing of minerals, coal, iron ore, flour, etc.



waste
reducing
product life



Scan to
learn about
protecting planet
information

Ningbo Fastest Safety Protection Products Co.,Ltd.

Rm. 1801 Jiamei Buliding, No.746 Taikang Zhong Rd., Yinzhou District, Ningbo China, 315199
TEL: +86-574-82822581 FAX: +86-574-82822578 EMAIL: ft@ftsafety.cn
Website: www.ftsafety.com